

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2003-243964  
(43)Date of publication of application : 29.08.2003

(51)Int.Cl.

H03H 9/64  
H03H 9/145

(21)Application number : 2002-040422  
(22)Date of filing : 18.02.2002


(71)Applicant : TOSHIBA CORP  
(72)Inventor : YAMASHITA TAKASHI  
KAWASE MINORU  
EHATA YASUO

## (54) SURFACE ACOUSTIC WAVE FILTER DEVICE

### (57)Abstract:

**PROBLEM TO BE SOLVED:** To provide a surface acoustic wave (SAW) filter device in which filter characteristics can be improved.

**SOLUTION:** A SAW element 8 provided in the SAW filter device has an input side interdigital converter 16 combining a comb-line electrode connected to an input terminal 20 and a comb-line electrode 16B connected to a ground terminal and an output side interdigital converter 15A combining a comb-line electrode 15B connected to an output terminal 21-1 and a comb-line electrode 15A connected to the ground terminal. An electrode finger 16A-EL for input, an electrode finger 15B-EL for output and electrode fingers 15A-EL and 16B-EL for grounding are arranged practically at equal intervals and in the prescribed interval between the electrode finger 16A-EL for input and the electrode finger 15B-EL for output, at least the two electrode fingers 15A-EL and 16B-EL for grounding are arranged.



decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office